

Diesel Fuel Treatment

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Date of issue: 03/28/2014

Revision date: 03/28/2014

Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Diesel Fuel Treatment
Product code : DFT-77CP

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Fuel Additive.

1.3. Details of the supplier of the safety data sheet

Justice Brothers, Inc.
2734 Huntington Drive
Duarte, CA - USA 91010
T (626) 359-9174 (M-F, 8am-5pm)

1.4. Emergency telephone number

Emergency number : CHEMTREC International +1 (703) 527-3887 24 hr

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable Liquid 4
Skin Irritation 2
Aspiration Toxicity 1

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

Combustible liquid. Causes skin irritation. May be fatal if swallowed and enters airways.

Precautionary statements (GHS-US) :

Keep away from flames and hot surfaces. – No smoking. Wear protective gloves/eye protection/face protection. Wash hands thoroughly after handling. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Petroleum Solvent	(CAS No) 64742-47-8	30 - 60	Flam. Liq. 3 Asp. Tox. 1
Petroleum Solvent	(CAS No) 64742-96-7	30 - 60	Flam. Liq. 4 Skin Irrit. 2 Asp. Tox. 1

The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation :

If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

Diesel Fuel Treatment

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

First-aid measures after skin contact	: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
First-aid measures after eye contact	: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. If irritation persists, get medical attention.
First-aid measures after ingestion	: If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: May cause respiratory tract irritation.
Symptoms/injuries after skin contact	: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.
Symptoms/injuries after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Treat for surrounding material.
Unsuitable extinguishing media	: None known.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Products of combustion may include, and are not limited to: oxides of carbon.
-------------	---

5.3. Advice for firefighters

Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Use special care to avoid static electric charges. Eliminate sources of ignition.
------------------	---

6.1.1. For non-emergency personnel

Protective equipment	: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.
----------------------	--

6.1.2. For emergency responders

No additional information available.

6.2. Methods and material for containment and cleaning up

For containment	: Eliminate sources of ignition. Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
Methods for cleaning up	: Scoop up material and place in a disposal container. Provide ventilation.

6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Keep away from sources of ignition. - No smoking. Avoid contact with skin and eyes. Avoid breathing vapour or mist. Do not swallow. When using do not eat, drink or smoke.
Hygiene measures	: Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep out of the reach of children. Keep container tightly closed and in a well-ventilated place. Keep cool.
--------------------	---

7.3. Specific end use(s)

Not available.

Diesel Fuel Treatment

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Petroleum Solvent (64742-47-8)		
USA ACGIH	ACGIH TWA	Not applicable
USA OSHA	OSHA PEL (TWA)	Not applicable

Petroleum Solvent (64742-96-7)		
USA ACGIH	ACGIH TWA	Not applicable
USA OSHA	OSHA PEL (TWA)	Not applicable

8.2. Exposure controls

Appropriate engineering controls	: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.
Hand protection	: Wear chemically resistant protective gloves.
Eye protection	: Safety glasses or goggles are recommended when using product.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Maintain levels below Community environmental protection thresholds.
Other information	: Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear.
Colour	: Yellow.
Odour	: Hydrocarbon.
Odour threshold	: No data available.
pH	: No data available.
Relative evaporation rate (butylacetate=1)	: No data available.
Melting point	: No data available.
Freezing point	: No data available.
Boiling point	: > 178.3 °C (> 353 °F)
Flash point	: 80 °C (176 °F)
Self ignition temperature	: No data available.
Decomposition temperature	: No data available.
Flammability (solid, gas)	: Flammable.
Vapour pressure	: No data available.
Relative vapour density at 20 °C	: No data available.
Relative density	: 0.82 g/cm ³
Solubility	: No data available.
Log Pow	: No data available.
Log Kow	: No data available.
Viscosity, kinematic	: 14 cSt @ 40 °C (104 °F)
Viscosity, dynamic	: No data available.
Explosive properties	: No data available.
Oxidising properties	: No data available.
Explosive limits	: No data available.

9.2. Other information

No additional information available

Diesel Fuel Treatment

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal storage conditions.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Heat. Incompatible materials. Sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Diesel Fuel Treatment	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	> 20 mg/l/4h (estimated)

Petroleum Solvent (64742-47-8)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	> 5.2 mg/l/4h

Petroleum Solvent (64742-96-7)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	> 5.28 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Based on available data, the classification criteria are not met.
Respiratory or skin sensitisation	: Based on available data, the classification criteria are not met.
Germ cell mutagenicity	: Based on available data, the classification criteria are not met.
Carcinogenicity	: Based on available data, the classification criteria are not met.
Reproductive toxicity	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (single exposure)	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (repeated exposure)	: Based on available data, the classification criteria are not met.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/injuries after inhalation	: May cause respiratory tract irritation.
Symptoms/injuries after skin contact	: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.
Symptoms/injuries after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability

Diesel Fuel Treatment	
Persistence and degradability	Not established.

Diesel Fuel Treatment

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

12.3. Bioaccumulative potential

Diesel Fuel Treatment

Bioaccumulative potential	Not established.
---------------------------	------------------

12.4. Mobility in soil

No additional information available.

12.5. Other adverse effects

No additional information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.

Additional information : Handle empty containers with care because residual vapours are flammable.

SECTION 14: Transport information

In accordance with DOT.

14.1. UN number

UN-No.(DOT) : NA1993

14.2. UN proper shipping name

DOT Proper Shipping Name : Combustible liquid, n.o.s. (Petroleum)

Department of Transportation (DOT) Hazard Classes : Combustible liquid

Packing group (DOT) : III

14.3. Additional information

Other information : No supplementary information available.

Special transport precautions : Do not handle until all safety precautions have been read and understood.

SECTION 15: Regulatory information

15.1. US Federal regulations

Petroleum Solvent (64742-47-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Petroleum Solvent (64742-96-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. US State regulations

No additional information available.

SECTION 16: Other information

Indication of changes : None.


Date of issue : 03/28/2014

Other information : None.

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product