

JB-80® Lubricant

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Date of issue: 06/18/2014

Revision date: 08/01/2014

Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : JB-80® Lubricant
Product code : JB-80

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Lubricant

1.3. Details of the supplier of the safety data sheet

Justice Brothers, Inc.
2734 Huntington Drive
Duarte, CA - USA 91010
T (626) 359-9174 (M-F, 8am-5pm)

1.4. Emergency telephone number

Emergency number : CHEMTREC International +1 (703) 527-3887 24 hr

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable Aerosols 2
Gases Under Pressure - Liquefied Gas
Skin Irritation 2
Skin Sensitisation 1
Aspiration Toxicity 1

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

Flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. May cause an allergic skin reaction. May be fatal if swallowed and enters airways.

Precautionary statements (GHS-US) :

Keep away from heat/sparks/open flames/hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash hands thoroughly after handling. Wear protective gloves. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing must not be allowed out of the workplace. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

12 % of the mixture consists of ingredient(s) of unknown acute toxicity.

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable.

JB-80® Lubricant

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Petroleum Solvent	(CAS No) 64742-47-8	10 - 30	Flam. Liq. 3 Asp. Tox. 1
Petroleum Solvent	(CAS No) 64742-96-7	10 - 30	Flam. Liq. 3 Skin Irrit. 2 Asp. Tox. 1
Petroleum Solvent	(CAS No) 64742-54-7	10 - 30	Asp. Tox. 1
Proprietary polymer	Proprietary	1 - 5	Not classified
Furan-2,5-dione, dihydro-, monopolyisobutylene derivatives	(CAS No) 67762-77-0	1 - 5	Eye Irrit. 2A
Phosphoric acid esters/amine salt	Proprietary	0.1 - 1	Acute Tox. 4 (Oral) Eye Dam. 1 Skin Sens. 1

* The specific chemical identity and exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
- First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. If irritation persists, get medical attention.
- First-aid measures after ingestion : If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause respiratory tract irritation.
- Symptoms/injuries after skin contact : Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin. May cause sensitisation by skin contact.
- Symptoms/injuries after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
- Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Treat for surrounding material.
- Unsuitable extinguishing media : None known.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon.
- Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

5.3. Advice for firefighters

- Firefighting instructions : Cool closed containers exposed to fire with water.
- Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Protective equipment : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.1.2. For emergency responders

No additional information available.

JB-80® Lubricant

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

6.2. Methods and material for containment and cleaning up

- For containment : Eliminate sources of ignition. Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
- Methods for cleaning up : Scoop up material and place in a disposal container. Vapours may be heavier than air and may travel along the ground to a distant ignition source and flash back. Provide ventilation.

6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from sources of ignition. - No smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Pressurized container: Do not pierce or burn, even after use.
- Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed.
- Storage conditions : Keep out of the reach of children. Do not expose to temperatures exceeding 50°C/ 122°F. Store away from direct sunlight or other heat sources.
- Storage area : Store in a well-ventilated place.

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Petroleum Solvent (64742-47-8)		
USA ACGIH	ACGIH TWA	Not applicable.
USA OSHA	OSHA PEL (TWA)	Not applicable.
Petroleum Solvent (64742-96-7)		
USA ACGIH	ACGIH TWA	Not applicable.
USA OSHA	OSHA PEL (TWA)	Not applicable.
Petroleum Solvent (64742-54-7)		
USA ACGIH	ACGIH TWA	Not applicable.
USA OSHA	OSHA PEL (TWA)	Not applicable.
Proprietary polymer		
USA ACGIH	ACGIH TWA	Not applicable.
USA OSHA	OSHA PEL (TWA)	Not applicable.
Furan-2,5-dione, dihydro-, monopolyisobutylene derivatives (67762-77-0)		
USA ACGIH	ACGIH TWA	Not applicable.
USA OSHA	OSHA PEL (TWA)	Not applicable.
Phosphoric acid esters/amine salt		
USA ACGIH	ACGIH TWA	Not applicable.
USA OSHA	OSHA PEL (TWA)	Not applicable.

8.2. Exposure controls

- Appropriate engineering controls : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.
- Hand protection : Wear chemically resistant protective gloves.
- Eye protection : Safety glasses or goggles are recommended when using product.
- Skin and body protection : Wear suitable protective clothing.

JB-80® Lubricant

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Maintain levels below Community environmental protection thresholds.
Other information	: Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Gas/Pressurized liquid.
Appearance	: Clear.
Colour	: Dark amber.
Odour	: Petroleum.
Odour threshold	: No data available.
pH	: No data available.
Relative evaporation rate (butylacetate=1)	: No data available.
Melting point	: No data available.
Freezing point	: No data available.
Boiling point	: > 178.3 °C (> 353 °F)
Flash point	: 80 °C (176 °F)
Self ignition temperature	: No data available.
Decomposition temperature	: No data available.
Flammability (solid, gas)	: Flammable.
Vapour pressure	: No data available.
Relative vapour density at 20 °C	: No data available.
Relative density	: 0.82 g/cm ³
Solubility	: No data available.
Log Pow	: No data available.
Log Kow	: No data available.
Viscosity, kinematic	: 14.0 cSt
Viscosity, dynamic	: No data available.
Explosive properties	: No data available.
Oxidising properties	: No data available.
Explosive limits	: No data available.

9.2. Other information

Flame projection = 0" ; Heat of combustion = 16097 BTU

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal storage conditions. Flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Heat. Incompatible materials. Sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

JB-80® Lubricant

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified.

JB-80® Lubricant	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	> 2000
LC50 inhalation rat	> 5 mg/l/4h

Petroleum Solvent (64742-47-8)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	> 5.2 mg/l/4h

Petroleum Solvent (64742-96-7)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	> 5.28 mg/l/4h

Petroleum Solvent (64742-54-7)	
LD50 oral rat	> 15000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 inhalation rat	> 5.53 mg/l/4h

Proprietary polymer	
LD50 oral rat	> 21500 µl/kg
LD50 dermal rabbit	> 10ml/kg

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Based on available data, the classification criteria are not met.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Based on available data, the classification criteria are not met.
Carcinogenicity	: Based on available data, the classification criteria are not met.
Reproductive toxicity	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (single exposure)	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (repeated exposure)	: Based on available data, the classification criteria are not met.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/injuries after inhalation	: May cause respiratory tract irritation.
Symptoms/injuries after skin contact	: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin. May cause sensitisation by skin contact.
Symptoms/injuries after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability

JB-80® Lubricant	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

JB-80® Lubricant	
Bioaccumulative potential	Not established.

12.4. Mobility in soil

No additional information available.

JB-80® Lubricant

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

12.5. Other adverse effects

- Effect on ozone layer : No additional information available
- Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

- Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.
- Additional information : Flammable vapours may accumulate in the container. Do not incinerate empty containers.

SECTION 14: Transport information

In accordance with DOT.

14.1. UN number

- UN-No.(DOT) : 1950

14.2. UN proper shipping name

- Proper Shipping Name (DOT) : Aerosols, flammable. Marine pollutant (Chlorinated paraffins)
- Department of Transportation (DOT) Hazard Classes : 2.1
- Hazard labels (DOT) :



- Marine pollutant : Yes

14.3. Additional information

- Other information : No supplementary information available.
- Special transport precautions : Do not handle until all safety precautions have been read and understood.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.


Alkanes, C18-28, chloro-	CAS No 85535-86-0 (listed under the TSCA entry CAS No 63449-39-8)
--------------------------	---

15.2. US State regulations

No additional information available.

SECTION 16: Other information

- Date of issue : 06/18/2014
- Revision date : 08/01/2014
- Other information : None.
- NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
- NFPA fire hazard : 3 - Liquids and solids that can be ignited under almost all ambient conditions.
- NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.